



Product Specification Manual

Product Name: **SV-W5NPEG**

Front



Back



Model	SV-W5NPEG
Product	5 Port Gigabit Switch
Fixed Port	5*10/100/1000Base-TX RJ45 port (Data)
Network Protocol	IEEE 802.3 IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T
Port Specification	10/100/1000BaseT (X) Auto
Transmission Mode	Store and Forward (full wire-speed)
Bandwidth	10Gbps
Packet Forwarding	7.2Mpps Supports 9K jumbo packet length forwarding at wire speed
MAC Address	2K
Buffer	2.5M
Transmission Distance	10BASE-T : Cat3,4,5 UTP (≤250 meter) 100BASE-TX : Cat5 or later UTP (150 meter) 1000BASE-TX : Cat6 or later UTP (150 meter)
Watt	Standby Power Consumption: ≤5W;
LED Indicator	PWR:Power LED 1-5:(Link LED=10/100MLink、1000M=Gigabit Link)
Power	External Power DC: 5V 2A
Operating Temperature/Humidity	-10~+55°C; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75°C; 5%~95% RH Non coagulation

Product size (L*W*H)	90mm*66mm*26mm
N.W/G.W (kg)	0.2kg/0.3kg
Installation	Desktop
Lightning protection level	3KV 8/20us; IP30
Certificate	CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;