



یوگالینک UG-4240

4G, LTE Modem-Router

یوگالینک UG-4240

▪ مودم روتر UG-4240 قابلیت استفاده از اینترنت 4G/LTE را دارد و با گذاشتن یک سیم کارت سائیز نانو در اسلات سیم کارت آن به راحتی می توان از اینترنت پر سرعت تا حداکثر 150 مگابیت بر ثانیه بهره مند شد. این مودم دارای چهار پورت شبکه از نوع 10/100 مگابیتی است که یک پورت آن WAN/LAN می باشد. همچنین دو آنتن WiFi داخلی و دو آنتن LTE خارجی نیز دارد.

قابلیت ها و مزایا

- مودم LTE به همراه شبکه بیسیم WiFi-300Mbps
- پشتیبانی از شبکه های FDD-LTE, TDD-LTE, WCDMA
- سرعت دانلود تا 150 مگابیت بر ثانیه / سرعت آپلود تا 50 مگابیت بر ثانیه
- مجهز به استانداردهای WiFi: IEEE 802.11 b/g/n
- قابلیت اتصال تا ۳۲ کاربر همزمان و به صورت بی سیم به مودم
- پشتیبانی از سرویس VPN کلاینت شامل PP2P/L2TP

Item	Description
Model Name	UG-4240
Technical Standard	Compatible with FDD-LTE, TDD-FDD, WCDMA
Frequency	LTE FDD: B1/B3/B7/B8/B20 LTE TDD: B40
Wi-Fi	2.4GHz, Wi-Fi 2*2MIMO, IEEE802.11 b/g/n Maximum Number of Device Connection: 32
Maximum Data Throughput	LTE CAT 4 FDD-LTE 150Mbps/50Mbps
MIMO	Support DL 2x2 MIMO
power consumption	<12W
Power Voltage	DC12V/1A
USIM/SIM	4FF nano SIM card
LED	Power Indication LED, WAN Signal Strength, Wi-Fi/WPS Indication LED, WAN/LAN Status LED, Internet Status LED
Antenna	2*External Detachable LTE antennas, 2*Internal WiFi antennas
Buttons	1 x Reset Button 1 x Power Button 1 x WPS Button
Ethernet	3*LAN Port, 1*WAN/LAN Port
SW Update	TR069/Local Update/FOTA
Wi-Fi Mode	AP mode only
Wi-Fi Security	OPEN & WPA-PSK & WPA2-PSK & WPA-PSK/WPA2-PSK
SMS	Support
IPv4	Support IPv4
IPv6	Support IPv6
Firewall	Mac/IP address filter, Port forwarding, Wi-Fi Black/White list
Data Statistics	Support
VPN Pass Through	PP2P/L2TP
Operating Temperature	Normal: 0°C to +40°C
Storage Temperature	-10°C to +60°C
Humidity	5%~ 95%